



## Flame-retardant Thin Wall Heat Shrinkable Tube



### Product Property and Application

UL approved tubing for all general purpose applications in electronic and electromechanical industries

**Standard: UL 224 VW-1**

**C-UL CSA C 22.2 OFT**

**Product No: H-1-TW**

**Operating Temperature: -55°C~125°C**

**Shrinking Temperature: Start at 70°C, and shrunk totally at 110°C**

**Shrink Ratio: 2:1      Rated Voltage: 300V**

**Available Color: Black, Red, Yellow, Green, Blue, White, Purple, and Grey.**

Part Number	Size		Standard Packing(m/spool)
	Inch	mm	
H-1-TW0016-X	1/16	1.6	200
H-1-TW0024-X	3/32	2.4	200
H-1-TW0032-X	1/8	3.2	200
H-1-TW0048-X	3/16	4.8	100
H-1-TW0064-X	1/4	6.4	100
H-1-TW0095-X	3/8	9.5	100
H-1-TW0127-X	1/2	12.7	100
H-1-TW0190-X	3/4	19	100
H-1-TW0254-X	1	25.4	50

For cut pieces, add "-000" to the end of the part number, showing the length, in mm.

Substitute colour code for X in the part number

Black 0; Brown 1; Red 2; Orange 3; Yellow 4; Green 5; Blue 6; Violet 7; Grey 8; White 9

Meg Wire Ltd, 139 Gatley Road, Gatley Cheadle, Cheshire. SK8 4PD. UK.  
Tel: +44 161 282 2805

[sales@megwire.co.uk](mailto:sales@megwire.co.uk)