



Flame-retardant Normal Wall Heat Shrinkable Tube



Product Property and Application

UL approved tubing for all general purpose applications in electronic and electromechanical industries

Standard: UL 224 VW-1

C-UL CSA C 22.2 OFT

Product No: H-1-NW

Operating Temperature: -55°C~125°C

Shrinking Temperature: Start at 70°C, and shrunk totally at 110°C

Shrink Ratio: 2:1 Rated Voltage: 600V

Available Color: Black, Red, Yellow, Green, Blue, White, Purple, and Grey.

Part Number	Size		Standard Packing(m/spool)
	Inch	mm	
H-1-NW0012-X	3/64	1.2	200
H-1-NW0016-X	1/16	1.6	200
H-1-NW0024-X	3/32	2.4	200
H-1-NW0032-X	1/8	3.2	200
H-1-NW0048-X	3/16	4.8	100
H-1-NW0064-X	1/4	6.4	100
H-1-NW0095-X	3/8	9.5	100
H-1-NW0127-X	1/2	12.7	100
H-1-NW0190-X	3/4	19	100
H-1-NW0254-X	1	25.4	50
H-1-NW0380-X	1 1/2	38	50
H-1-NW0510-X	2	51	25
H-1-NW0760-X	3	76	25
H-1-NW1020-X	4	102	25

For cut pieces, add "-000" to the end of the part number, showing the length, in mm.

Substitute colour code for X in the part number

Black 0; Brown 1; Red 2; Orange 3; Yellow 4; Green 5; Blue 6; Violet 7; Grey 8; White 9

Meg Wire Ltd, 139 Gatley Road, Gatley Cheadle, Cheshire. SK8 4PD. UK.
Tel: +44 161 282 2805

sales@megwire.co.uk