

UL21476 Multi-conductor Shielded Cable 多芯屏蔽电缆

Stranded bare or tinned copper conductor, PE insulation,

Aluminum mylar shield, mPPE-PE jacket

导体使用绞合裸铜或镀锡铜线, 聚乙烯绝缘, 铝箔麦拉带屏蔽, 改性聚苯醚-聚乙烯护套

PRODUCT DESCRIPTION 产品说明



E148000 AWM STYLE 21476 AWG NO. 80°C 30V VW-1 --- c AWM I/II A/B 80°C 30V FT1 -HF- -LF- PCXX LTK

- Rated temperature 额定温度 : 80°C
- Rated voltage 额定电压 : 30V
- Reference standard 参考标准 :
UL 758, UL1581 & CSA C22.2 No. 210
- Passes UL VW-1 & CSA FT1 vertical flame test
通过 UL VW-1 及 CSA FT1 垂直耐燃测试

Conductor 导体			Insulation 绝缘		Jacket 护套	Max. DC Resistance at 20°C 最大电阻 (ohm/km)
No. of Cores 芯数	AWG 线规	No./mm 绞数/线径	Thickness 厚度 (mm)	Diameter 外径 (mm)	Diameter 外径 (mm)	
3	28	7/0.127	0.26	0.90	3.20	239
4	28	7/0.127	0.26	0.90	3.50	239
5	28	7/0.127	0.26	0.90	3.70	239
6	28	7/0.127	0.26	0.90	4.00	239
8	28	7/0.127	0.26	0.90	4.30	239
3	26	7/0.16	0.26	1.00	3.40	150
6	26	7/0.16	0.26	1.00	4.30	150
9	26	7/0.16	0.26	1.00	5.20	150
5	24	7/0.20	0.26	1.12	4.40	94.2

UL21515 Flat Ribbon Wire 排线

Stranded bare or tinned copper conductor, 36-14 AWG, mPPE insulation

导体使用 36-14 AWG 绞合裸铜或镀锡铜线, 改性聚苯醚绝缘

PRODUCT DESCRIPTION 产品说明



E148000 AWM STYLE 21515 AWG NO. 105°C 300V VW-1 --- c AWM I A/B 105°C 300V FT1 -HF- -LF- PCXX LTK

- Rated temperature 额定温度 : 105°C
- Rated voltage 额定电压 : 300V
- Reference standard 参考标准 :
UL 758 & UL1581
- Passes UL VW-1 vertical flame test
通过 UL VW-1 垂直耐燃测试

Conductor 导体			Insulation 绝缘		Max. DC Resistance at 20°C 最大电阻 (ohm/km)
No. of Cores 芯数	AWG 线规	No./mm 绞数/线径	Thickness 厚度 (mm)	Diameter 外径 (mm)	
3	28	7/0.127	0.23	0.90x2.70	239
4	28	7/0.127	0.23	0.90x3.60	239
5	28	7/0.127	0.23	0.90x4.50	239
6	28	7/0.127	0.23	0.90x5.40	239
7	28	7/0.127	0.23	0.90x6.30	239
8	28	7/0.127	0.23	0.90x7.20	239
9	28	7/0.127	0.23	0.90x8.10	239
10	28	7/0.127	0.23	0.90x9.00	239
11	28	7/0.127	0.23	0.90x9.90	239
12	28	7/0.127	0.23	0.90x10.80	239
3	26	7/0.16	0.23	1.00x3.00	150
4	26	7/0.16	0.23	1.00x4.00	150
5	26	7/0.16	0.23	1.00x5.00	150
6	26	7/0.16	0.23	1.00x6.00	150
7	26	7/0.16	0.23	1.00x7.00	150
8	26	7/0.16	0.23	1.00x8.00	150
9	26	7/0.16	0.23	1.00x9.00	150
10	26	7/0.16	0.23	1.00x10.00	150
11	26	7/0.16	0.23	1.00x11.00	150
12	26	7/0.16	0.23	1.00x12.00	150

1. Only part of products are listed above.
以上表格只列出一部份产品。
2. The above information is for reference only, and is subject to the final specification.
以上数字仅为参考值, 数字以最终规格书为准。

